



3608, 3628 8K (1K X 8) BIPOLAR PROM

PRELIMINARY
Notice: This is not a final specification. Some parametric limits are subject to change.

OLD


3608, 3628	80 ns Max.
3608-4, 3628-4	100 ns Max.

- Fast Access Time: 65 ns Typically
- Low Power Dissipation: 0.09mW/Bit Typically
- Four Chip Select Inputs for Easy Memory Expansion
- Open Collector (3608) and Three-State (3628) Outputs
- Hermetic 24-Pin DIP
- Polycrystalline Silicon Fuses for Higher Fuse Reliability


The Intel® 3608/3628 are fully decoded 8192 bit PROMs organized as 1024 words by 8 bits. The worst case access time of 80 ns is specified over the 0°C to 75°C temperature range and 5 percent V_{CC} power supply tolerances. There are four chip selects provided to facilitate expanding 3608/3628s into larger PROM arrays. The PROMs are a Schottky clamped TTL memory array with polycrystalline silicon fuses. All outputs are initially high and logic low levels can be electrically programmed in selected bit locations.

Prior to the 8192 bit 3608/3628, the highest density bipolar PROM available was 4096 bits. The high density of the 3608/3628 now easily doubles the capacity without an increase in area on existing designs currently using 512 words by 8 bit PROMs. There is also little, if any, penalty in power since the 3608/3628 power/bit is approximately one-half that of 4K PROMs. The 3608/3628 are packaged in a hermetic 24-pin dual in-line package.


PIN CONFIGURATION



BLOCK DIAGRAM



LOGIC SYMBOL



PIN NAMES

$A_0 - A_9$	ADDRESS INPUTS
$CS_1 - CS_4$	CHIP SELECT INPUTS ^[1]
$O_1 - O_8$	DATA OUTPUTS

[1] To select the PROM $\overline{CS}_1 = \overline{CS}_2 = V_{IL}$
and $CS_3 = CS_4 = V_{IH}$

ABSOLUTE MAXIMUM RATINGS*

Temperature Under Bias -65°C to $+125^{\circ}\text{C}$
 Storage Temperature -65°C to $+160^{\circ}\text{C}$
 Output or Supply Voltages -0.5V to 7 Volts
 All Input Voltages -1V to 5.5V
 Output Currents 100mA

***COMMENT**

Stresses above those listed under "Absolute Maximum Rating" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or at any other condition above those indicated in the operational sections of this specification is not implied.

D.C. CHARACTERISTICS: All Limits Apply for $V_{CC} = +5.0\text{V} \pm 5\%$, $T_A = 0^{\circ}\text{C}$ to $+75^{\circ}\text{C}$

Symbol	Parameter	Limits				Test Conditions
		Min.	Typ.[1]	Max.	Unit	
I_{FA}	Address Input Load Current		-0.05	-0.25	mA	$V_{CC}=5.25\text{V}$, $V_A=0.45\text{V}$
I_{FS}	Chip Select Input Load Current		-0.05	-0.25	mA	$V_{CC}=5.25\text{V}$, $V_S=0.45\text{V}$
I_{RA}	Address Input Leakage Current			40	μA	$V_{CC}=5.25\text{V}$, $V_A=5.25\text{V}$
I_{RS}	Chip Select Input Leakage Current			40	μA	$V_{CC}=5.25\text{V}$, $V_S=5.25\text{V}$
V_{CA}	Address Input Clamp Voltage		-0.9	-1.5	V	$V_{CC}=4.75\text{V}$, $I_A=-10\text{mA}$
V_{CS}	Chip Select Input Clamp Voltage		-0.9	-1.5	V	$V_{CC}=4.75\text{V}$, $I_S=-10\text{mA}$
V_{OL}	Output Low Voltage		0.3	0.45	V	$V_{CC}=4.75\text{V}$, $I_{OL}=15\text{mA}$
I_{CEX}	3608 and 3608-4 Output Leakage Current			100	μA	$V_{CC}=5.25\text{V}$, $V_{CE}=5.25\text{V}$
I_{CC}	Power Supply Current		150	190	mA	$V_{CC}=5.25\text{V}$, $V_{A0} \rightarrow V_{A9}=0\text{V}$, PROM deselected
V_{IL}	Input "Low" Voltage			0.85	V	$V_{CC}=5.0\text{V}$
V_{IH}	Input "High" Voltage	2.0			V	$V_{CC}=5.0\text{V}$

3628,3628-4 ONLY

Symbol	Parameter	Min.	Typ.[1]	Max.	Unit	Test Conditions
I_{O1}	Output Leakage for High Impedance State			100	μA	$V_O=5.25\text{V}$ or 0.45V , $V_{CC}=5.25\text{V}$, $\overline{CS}_1=\overline{CS}_2=2.4\text{V}$
$I_{SC}^{[2]}$	Output Short Circuit Current	-15	-25	-60	mA	$V_{CC}=5.00\text{V}$, $T_A=25^{\circ}\text{C}$, $V_O=0\text{V}$
V_{OH}	Output High Voltage	2.4	3.4		V	$I_{OH}=-2.4\text{mA}$, $V_{CC}=4.75\text{V}$

NOTES: 1. Typical values are at 25°C and at nominal voltage.
 2. Unmeasured outputs are open during this test.

A.C. CHARACTERISTICS

$V_{CC} = +5V \pm 5\%$, $T_A = 0^\circ C$ to $+75^\circ C$

SYMBOL	PARAMETER	MAX. LIMITS		UNIT	CONDITIONS
		3608 3628	3608-4 3628-4		
t_A	Address to Output Delay	80	100	ns	$\overline{CS}_1 = \overline{CS}_2 = V_{IL}$ and $CS_3 = CS_4 = V_{IH}$ to select the PROM.
t_{EN}	Output Enable Time	40	45	ns	
t_{DIS}	Output Disable Time	40	45	ns	

CAPACITANCE⁽¹⁾

$T_A = 25^\circ C$, $f = 1$ MHz

SYMBOL	PARAMETER	TYP. LIMITS	UNIT	TEST CONDITIONS
C_{INA}	Address Input Capacitance	4	pF	$V_{CC} = 5V$ $V_{IN} = 2.5V$
C_{INS}	Chip-Select Input Capacitance	6	pF	$V_{CC} = 5V$ $V_{IN} = 2.5V$
C_{OUT}	Output Capacitance	7	pF	$V_{CC} = 5V$ $V_{OUT} = 2.5V$

NOTE 1: This parameter is only periodically sampled and is not 100% tested.

SWITCHING CHARACTERISTICS

Conditions of Test:

Input pulse amplitudes - 2.5V

Input pulse rise and fall times of


5 nanoseconds between 1 volt and 2 volts

Speed measurements are made at 1.5 volt levels

Output loading is 15 mA and 30 pF


Frequency of test - 2.5 MHz

15mA TEST LOAD




WAVEFORMS

ADDRESS TO OUTPUT DELAY



CHIP SELECT TO OUTPUT DELAY





3065 Bowers Avenue
Santa Clara, California 95051
Tel: (408) 246-7501
TWX: 910-338-0026
TELEX: 34-6372

SALES AND MARKETING OFFICES

U.S. AND CANADIAN SALES OFFICES

ALABAMA

Glen White Associates
7844 Horseshoe Trail
Huntsville 35802
Tel: (205) 863-9394

ARIZONA

Sales Engineering, Inc.
7155 E. Thomas Road, No. 6
Scottsdale 85252
Tel: (602) 945-5781
TWX: 910-950-1288

CALIFORNIA

Intel Corp.*
990 E. Arques Ave.
Suite 112
Sunnyvale 94086
Tel: (408) 738-3870
TWX: 910-339-9279
TWA: 910-338-0255

Mac-I

P.O. Box 1420
Cupertino 95014
Tel: (408) 257-9880
Earle Associates, Inc.
4433 Convey Street
Suite A
San Diego 92111
Tel: (714) 278-5441
TWX: 910-335-1585

Intel Corp.*

1651 East 4th Street
Suite 228
Santa Ana 92701
Tel: (714) 835-9642
TWX: 910-595-1114

COLORADO

Intel Corp.
12075 East 45th Avenue
Suite 310
Denver 80239
Tel: (303) 373-4920
TWX: 910-932-0322

CONNECTICUT

Intel Corp.
8 Mill Plain Road
Danbury 06810
Tel: (203) 792-8366

EUROPEAN MARKETING OFFICES

BELGIUM

Intel International*
Rue du Moulin à Papier
51-Boile 1
B-1160 Brussels
Tel: (02) 660 30 10
TELEX: 24814

FRANCE

Intel Corporation, S.A.R.L.*
74, Rue D'Arcueil
Siliic 223
94528 Rungis Cedex
Tel: (01) 687 22 21
TELEX: 270475

SCANDINAVIA

Intel Scandinavia A/S*
Lyngbyvej 32 2nd Floor
DK-2100 Copenhagen East
Denmark
Tel: (01) 18 20 00
TELEX: 19567
Intel Sweden AB*
Box 86
S-16212 Vällingby 1
Sweden
Tel: (08) 37 53 70
TELEX: 13164 (ABCENT)

ENGLAND

Intel Corporation (U.K.) Ltd.*
Broadfield House
4 Between Towns Road
Cowley, Oxford OX4 3NB
Tel: (0865) 77 14 31
TELEX: 837203
Intel Corporation (U.K.) Ltd.
46-50 Bean Street
Nantwich, Cheshire CW5 5LJ
Tel: (0270) 62 65 60
TELEX: 36620

GERMANY

Intel Semiconductor GmbH*
Seidlstrasse 27
8000 Muenchen 2
Tel: (089) 55 81 41
TELEX: 523 177
Intel Semiconductor GmbH
D-6272 Niederrhausen
Wiesenweg 26
Tel: (06127) 2314
TELEX: 04186183
Intel Semiconductor GmbH
D-7000 Stuttgart 80
Ernstthalderstrasse 17
Tel: (0711) 7351506
TELEX: 7255346

ORIENT MARKETING OFFICES

JAPAN

Intel Japan Corporation*
Flower Hill-Shinmachi East Bldg.
1-23-9, Shinmachi, Setagaya-ku
Tokyo 154
Tel: (03) 426-9261
TELEX: 781-28426

HONG KONG

QI (Far East) Ltd.
Tak Yan Commercial Bldg. 6th floor
30-32 D'Agullar Street, Central
Hong Kong
Tel: 5-260311
TELEX: 83138 JADE HX

TAIWAN

Taiwan Automation Co.*
6th Floor, 18-1, Lane 14
Chi-Lin Road
Taipei
Tel: (02) 551726-9
TELEX: 11942 TAIAUTO

TAIWAN (cont.)

Asionics-Taiwan, Inc.
205 Pa-Teh Road, Section 4
Taipei
Tel: 75 55 82
TELEX: 22158 Asionics

INTERNATIONAL DISTRIBUTORS

AUSTRALIA

A. J. Ferguson (Adelaide) PTY, Ltd.
44 Prospect Rd.
Prospect 5082
South Australia
Tel: 269-1244
TELEX: 82635

Warburton O'Donnell Limited
372 Eastern Valley Way
Chatswood, N.S.W. 2067
Tel: 407 3261
TELEX: WARFRAN AA 21299

AUSTRIA

Bacher Elektronische Geräte GmbH
Meldinger Hauptstrasse 78
A 1120 Vienna
Tel: (0222) 83 83 96
TELEX: (01) 1532

BELGIUM

Inelco Belgium S.A.
Avenue Val Duchesse, 3
B-1160 Brussels
Tel: (02) 660 00 12
TELEX: 25441

DENMARK

Scandinavian Semiconductor
Supply A/S
Nannasgade 18
DK-2200 Copenhagen N
Tel: (01) 93 50 90
TELEX: 19037

FINLAND

Oy Fintronic AB
Loennrotinkatu 35D
SF 00180
Helsinki 18
Tel: (00) 164 451
TELEX: 12426

FRANCE

Tekeltec Airtronic
Cite des Bruyeres
Rue Carle Vernet
92310 Sevres
Tel: (1) 027 75 35
TELEX: 250997

GERMANY

Alfred Neye Enatechnik GmbH
Schillerstrasse 14
D-2085 Quickborn-Hamburg
Tel: (04108) 6121
TELEX: 02-13590
Electronite 2000 Vertriebs GmbH
Neumarkter Strasse 75
D-8000 Muenchen 80
Tel: (089) 434061
TELEX: 484426

Jermyn GmbH

Postfach 1146
D-6277 Kamberg
Tel: (06434) 8005
TELEX: 484426

HONG KONG

ASTEC International
Keystone House, 2nd Floor
Hankow Road, Kowloon
Tel: 3-687780
TELEX: 74899 ASCOM

ISRAEL

Eastronics Ltd.*
11 Rozanis Street
P.O. Box 39300
Tel-Aviv
Tel: 475151
TELEX: 33638

ITALY

Eledra 3S S.P.A.
Viale Elvezia, 18
20154 Milan
Tel: (02) 3493041
TELEX: 99332
Eledra 3S S.P.A.
Via Giuseppe Vaimarano, 63
00139 Rome, Italy
Tel: (06) 81 27 290 - 81 27 324

JAPAN

Pan Electron
No. 1 Higashikata-Machi
Midori-Ku, Yokohama 226
Tel: (045) 471-8811
TELEX: 781-4773
Ryoyo Electric Corp.
Konwa Bldg.
1-12-22, Tsukiji, 1-Chome
Chuo-Ku, Tokyo 104
Tel: (03) 543-7711

NETHERLANDS

Inelco Nederland
AFD Elektronik
Joan Muiskenweg 22
NL-1008 Amsterdam
Tel: (020) 934824
TELEX: 14622

NORWAY

Nordisk Elektronik (Norge) A/S
Mustads Vel 1
N-050 2
Tel: (02) 55 38 93
TELEX: 16963

SOUTH AFRICA

Electronic Building Elements
P.O. Box 4609
Pretoria
Tel: 78 92 21
TELEX: 30181

SPAIN

Interface
Ronda San Pedro 22
Barcelona 10
Tel: 301 78 51

SWEDEN

Nordisk Elektronik AB
Fack
S-10380 Stockholm 7
Tel: (08) 248340
TELEX: 10547

SWITZERLAND

Industrie AG
Gemsenstrasse 2
Postchock 80 - 21190
CH-8021 Zurich
Tel: (01) 60 22 30
TELEX: 56788

UNITED KINGDOM

Rapid Recall, Ltd.
11-15 Betterton Street
Drury Lane
London WC2H 9BS
Tel: (01) 378-6741
TELEX: 28752
G.E.C. Semiconductors Ltd.
East Lane
Wembley HA9 7PP
Middlesex
Tel: (01) 804-9303
TELEX: 923429
Jermyn Industries
Vestry Estate
Sevenoaks, Kent
Tel: (0732) 50144
TELEX: 95142

*Field Application Location